




NEOBUS

Novosadska fabrika autobusa



Dimensions:



A	B	C	D	E	F	G	H
6300mm	12000mm	3530mm	2500mm	2530mm	3170mm	2089mm	1837mm

Equipment:



Double air circut
DISK/EBS/ABS/ASR



"Dynafleet system"



Optional equipment
and engines

Technical data:

Type	Interurban
Chassis	NEOBUS, self-carrying
Engine	CUMMINS ISBe4 - 300 Euro 4
Engine type, Cyl. Nr.	inline, 6
Bore/Stroke	Ø 107/124 mm
Displacement	6700 cm ³
Output	221 kW (300 KS), 2500 rpm
Max. torque	1100 Nm, 1200-1700 rpm
Position in vehicle	back, standing
Clutch	Inside gearbox
Gearbox	Allison automatic TR350R
Transmission ratio	i = 4,875
Retarder	Inside gearbox
Steering	Servo-hydraulic
Front axle	FAP VO4/13DL-7, air suspension
Rear axle	FAP HO4/01DL-10, air suspension
Min. turning	24m
Max. wheel angle	48°
Rims	8,25" x 22,5"
Tyres	295/80 R22.5
Batteries	2 x 12V / 170 Ah
Altenator	2 x 80A
Fuel tank	290 L
Max. speed	110 km/h
Max. climbing ability	25%
Luggage vol.	6 m ³
Total passengers	51 + 1 + 1